

MATERIAL SAFETY DATA SHEET
ENERGY MIZER
295 EDWARDIA DR.
GREENSBORO, NC 27409

HIMIS RATINGS
Health: 2
Flammability: 4
Reactivity: 0
Personal Protection: G

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: STAINLESS STEEL CLEANER AND POLISH
Chemical Family: Aerosol
Company Identification: Energy Mizer
P.O. Box 10124
Greensboro, NC 27404

Emergency Telephone Number: {800-852-4650}
Date Prepared: December 7, 2005
MSDS Number: RA-505
MFGD By: ABC Compounding Co., Inc.
6970 Jonesboro Rd.
Morrow, GA. 30260

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS NUMBER	CHEMICAL NAME	% BY WEIGHT	OSHA PEL ACGIH TLV	SARA 302/304 (1) *	SARA 313 (2) *	STATE INFO (3) (4)
64742-47-8	Aliphatic Hydrocarbon	< 16.0	300ppm / 300ppm	NO	NO	NO
6472-52-5	Severely Hydro treated Heavy Naphthenic	< 41.0	5 mg/ m3 (oil mist)	NO	NO	NO
5989-27-5	D'limonene	< 24.0	n/e n/e	NO	NO	NO
-	Propellent Mixture	-	-	-	-	-
74-98-6	Propane	-	100 ppm	NO	NO	NO
106-97-8	N-Butane	-	600 ppm	NO	NO	NO

* See Section 15 for more information n/e = none established - N/A = not applicable

Section 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER! Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

Primary Route of Entry: Skin contact, inhalation

Acute/Potential Health Effects:

EYES: May cause mild eye irritation. Symptoms include stinging, tearing and redness.
SKIN: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns
INHALATION: High vapor/ aerosol concentration (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, Anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/ or damage.
INGESTION: Harmful or fatal if swallowed. Aspiration hazard – this material can enter lungs during swallowing or vomiting and cause lung Inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolong occupational overexposure to solvents with permanent brain and Nervous system damage.

Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of Material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (Nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea , headache, and/or unconsciousness.)

Target Organ Effects: No data.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by the IARC, NTP, or OSHA

Section 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash Clothing before reuse. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because This material can enter the lungs and cause severe lung damage. Do not leave individual unattended.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 120F (TCC Method). Flame Extension: >18", Positive Flashback

Extinguishing Media: Dry chemical, CO2 or Foam is recommended

Special Fire Fighting Instructions: **EXTREAMLY FLAMMABLE.** Contents under pressure. Cool exposed containers with water spray, to prevent bursting. SCBA should be used whenever chemical fires are present.

Section 6: ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse Vapors with water spray. Prevent runoff from entering drains, sewers, streams, or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7: HANDLING AND STORAGE

Do not use or store near heat, sparks, or open flame. Exposure to temperatures above 120 F. may cause bursting. Do not puncture or incinerate container. Store in a cool dry place. Do not get into eyes, on skin, or in clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Section 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves, (made from rubber, nitrile, or neoprene.)

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z00.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear, colorless spray/mist with citrus odor

Solubility in Water: Negligible

Evaporation Rate (Butyl Acetate=1): n/e

Specific Gravity [H₂O=1] : 0.85

pH Concentrate: n/a

Vapor Pressure [mmHg]: n/e

Vapor Density [Air=1]: n/e

Boiling Point: n/a

Section 10: REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to avoid: High temperature

Hazardous Decomposition Products: CO, CO₂

Incompatibility: Acids and strong oxidizers.

Section 11: TOXICOLOGICAL INFORMATION

No data

Section 12: ECOLOGICAL INFORMATION

No data

Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Waste must be disposed of in accordance with federal, state, and local environmental control regulations. See label for further instructions.

Section 14: TRANSPORTATION INFORMATION

D.O.T Shipping Name / Class:

Consumer Commodity, ORM-D

(Domestic Ground Shipments)

Section 15: REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA (Toxic Substance Control Act) : The intentional ingredients of product are listed

Title III Section 311/312 Hazardous Categories – 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

(1) Title III Sections 313

(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65 if indicated under Section 2 of this MSDS, this product contains toxin rhAmica7s subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s) D001

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations. (3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986) (4) Massachusetts (Hazardous Substance Disclosure by Employers)

Section 16: OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive or fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.